



## DECLARATION OF PERFORMANCE

### N° 04-CPR-MP80

- 1) Unique identification code of the product-type:  
**Metal chimney system “MONO ECO 80”**
- 2) Intended use of the product, in conformity with the applicable standard:  
**Metal chimney to convey the products of combustion from heating appliances to the outside atmosphere.**
- 3) Name and address of the Manufacturer: **M.T. s.r.l.**  
**Manufacturing site: Via I° Maggio 19, 31040 Giavera del Montello (Treviso) - Italy**  
**Registered office: Via Castel di Sotto 2, 31040 Giavera del Montello (Treviso) - Italy**
- 4) Name and address of the authorized representative or representative: **Not applicable**
- 5) System of assessment and verification of constancy of the product performance (VVCP): **System 2+ and 4.**
- 6) The notified certification body Kiwa Cermet Italia S.p.a., with identification number 0476, performed under the system 2+ the initial inspection of the manufacturing plant in the factory and carries out the continuous surveillance activity for the assessment and verification of the factory production control, issuing a certificate of conformity of the factory production control according to EN1856-1:2009 standard.
- 7) Appropriate technical documentation and / or specific technical documentation: **Not applicable.**
- 8) Declared performance according to the harmonized standard EN 1856-2:2009:

*Designation 1:* **EN1856-2:2009 - T200 P1 W V2 L50080 Oxxx**

*Designation 2:* **EN1856-2:2009 - T200 N1 D V2 L50080 Oyyy**

*Designation 3:* **EN1856-2:2009 - T600 N1 D V2 L50080 Gzzz**

As for the mandatory distances from combustible materials, they vary according to the nominal internal diameter of the chimney in question, according to the following scheme:



NOMINAL DIAMETER (mm)	Distance under normal operating conditions (xxx) in mm	Distance under normal operating conditions (yyy) in mm	Distance in conditions of soot fire (zzz) in mm
D.120 to D.300	75	400	600M
D.301 to D. 450	115	600	900M
D.451 to D.600	150	800	1200M
Above 600	300	1600	2400M

Essential Characteristics	Performance	Harmonized technical standard
Nominal diameters of the system <b>MONO ECO 80</b> (mm):	Ø 150, 160, 180, 200, 230, 250, 300, 350, 400, 450, 500, 600, 700, 750, 800, 850, 900.	<b>EN 1856-2:2009</b>
Type of material	Metal wall: stainless steel AISI 316L, thickness 8/10.	
Compressive strength	Positive outcome. Chimney supports resistant to compressive strength according to Par. 6.2.1.2 of the standard, both stainless steel and copper.	
Soot fire resistance	Related to the nominal diameter (see table on page 1): Designation 1: O75, O115, O150, O300; Designation 2: O400, O600, O800, O1600; Designation 3: G600M, G900M, G1200M, G2400M.	
Gas tightness	Designation 1: P1; Designations 2-3: N1.	
Roughness coefficient	0,02 mm (declared).	
Flow resistance of the components	According to EN13384-1.	
Thermal resistance	0,2 m <sup>2</sup> K/W, declared.	
Thermal shock resistance	Positive outcome: class G.	
Non vertical installation	Yes, maximum angle 90°.	
Components subjected to wind load	Distance between consecutive vertical supports: 3 meters	
Vapour and condensate durability	Positive outcome: class W.	
Durability against corrosion	Class V2.	
Freeze thaw resistance	Yes.	

The performance of the product identified above is in conformity with the set of declared performance. This declaration of responsibility is issued, in accordance with Regulation (UE) n. 305/2011 and delegated regulation No. 574/2014 - Annex III, under the sole responsibility of the manufacturer identified at Par. 4.

Signed for and on behalf of the manufacturer by Mr. Romano Caoduro, Sole Administrator of company M.T. s.r.l.

Giavera del Montello, 1st June 2022

